

View Online at <https://aerobasegroup.com/nsn/5305-01-264-5836>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

2.030 inches

**Head Style:**

Hexagon

**Head Height:**

0.193 inches

**Width Between Flats:**

0.375 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.190 inches

**Width Across Flats:**

0.156 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Special Features:**

Furnish with stop nut a-286 cres per ams 5731, passivate per qq-p-35, 140000 p.S.I. Min ams5529; coil spring 18-8 type 302 cres per astm a580, passivate; spring cup 18-8 type 300 cres per astm-a-555, astm-a-581 ams 5640; disc spring 17-7 ph cres per ams 5529, 240000 p.S.I. Min per ams 5529, passivate; also contains self-locking slug round per mil-f-18240

**Material:**

Steel comp 301 stand-off or steel comp 302 stand-off or steel comp 304 stand-off or steel comp 316 stand-off or steel comp 303 plus x stand-off or steel comp 303se stand-off or steel comp 303pb stand-off

**Material Specification:**

Mil-s-5059 military specification single material response primary washer

**Surface Treatment:**

Passivate stand-off

**Surface Treatment Specification:**

Qq-p-416 type 1 cl 2 federal specification single treatment response fastener

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5059 spec.