## NSN 5305-01-264-5864



Assembled Washer Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-264-5864 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.688 inches and 0.750 inches **Fastener Length:** 0.750 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 40.0 rockwell c primary washer and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.365 inches and 0.381 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.018 inches and 0.024 inches Material: Steel comp 1050 primary washer or steel comp 1053 primary washer or steel comp 1054 primary washer or steel comp 1055 primary washer or steel comp 1059 primary washer or steel comp 1060 primary washer or steel comp 1551 primary washer or steel comp 1552 primary washer or steel comp 1561 primary washer or steel comp 1566 primary washer **Surface Treatment:** Cadmium or zinc **Thread Series Designator:** Unf Shelf Life: N/a

No

**Unit Of Measure:** 

**Demilitarization:** 

## NSN 5305-01-264-5864

Assembled Washer Screw - Page 2 of 2



Fiig:

A003b0