Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-264-5873



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.288 inches and 0.380 inches Fastener Length: Between 0.350 inches and 0.380 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches Locking Feature: Pellet threads or strip threads or patch threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c fastener and 40.0 rockwell c fastener Surface Finish: 32.0 microinches threads **Product Name:** Navy special project Material: Plastic locking feature **Material Specification:** Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener Surface Treatment: Cadmium fastener and chromate fastener **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response fastener **Thread Series Designator:** Unjf

Specification Data:

80205-nas8103 professional/industrial association standard

NSN 5305-01-264-5873

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

