## NSN 5305-01-264-6363



Externally Relieved Body Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-264-6363 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.190 inches **Fastener Length:** Between 0.796 inches and 0.828 inches **Head Style:** Fillister **Head Diameter:** Between 0.250 inches and 0.260 inches **Head Height:** Between 0.133 inches and 0.156 inches **First Diameter From Head:** 0.120 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.606 inches and 0.638 inches **Point Style:** Flat **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Product Name:** Navy special project Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 361 or steel comp comp 385 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** 

**Unit Of Measure:** 

Shelf Life:

Unc

N/a

## NSN 5305-01-264-6363

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0