NSN 5305-01-264-6368

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-264-6368 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.381 inches and 0.431 inches **Fastener Length:** Between 1.203 inches and 1.233 inches **Head Style:** Flat countersunk **Head Diameter:** 0.338 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp xm-13 **Screw Material Specification:** Ams 5629 assn standard single material response **Screw Surface Treatment:** Aluminum and chromate **Screw Surface Treatment Specification:** Mil-c-83488 type 2 cl 3 military specification single treatment response **Special Features:** Cetyl alcohol per mil-l-87132 type 1 grade 8 **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A500d0

NSN 5305-01-264-6368

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-83488 spec.