NSN 5305-01-264-6372

Thread Class:

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-264-6372

| Inread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.357 inches and 0.438 inches |
| Fastener Length: |
| Between 0.407 inches and 0.438 inches |
| Head Style: |
| Fillister |
| Head Diameter: |
| Between 0.178 inches and 0.183 inches |
| Head Height: |
| Between 0.059 inches and 0.069 inches |
| Locking Feature: |
| Pellet threads or strip threads or patch threads |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.112 inches |
| Thready Qty Per Inch (tpi): |
| 40 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 36.0 rockwell c fastener and 40.0 rockwell c fastener |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Plastic locking feature |
| Material Specification: |
| Ams 5737 assn standard single material response fastener |
| Surface Treatment: |
| Passivate fastener |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response fastener |
| Thread Series Designator: |
| Unjc |
| Specification Data: |
| 80205-nas1191 professional/industrial association standard |
| Shelf Life: |
| N/a |
| |

NSN 5305-01-264-6372

Socket Head Cap Screw - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0