

View Online at <https://aerobasegroup.com/nsn/5305-01-264-6376>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.547 inches and 1.750 inches

**Fastener Length:**

Between 1.690 inches and 1.750 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.642 inches and 0.656 inches

**Head Height:**

Between 0.430 inches and 0.438 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.438 inches

**Width Across Flats:**

0.375 inches

**Thready Qty Per Inch (tpi):**

14

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 45.0 rockwell c

**Minimum Yield Strength:**

155000 pounds per square inch

**Product Name:**

Screw, cap, socket head

**Material:**

Steel comp 4340

**Material Specification:**

Astm a574 assn standard single material response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

2 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-1222 spec.