

View Online at <https://aerobasegroup.com/nsn/5305-01-264-8869>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.140 inches

**Fastener Length:**

0.285 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 0.212 inches and 0.226 inches

**Head Height:**

Between 0.053 inches and 0.083 inches

**Internal Drive Style:**

Slot

**Material Accommodated Thickness:**

Between 0.031 inches and 0.062 inches

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Color:**

Black stand-off

**Material:**

Steel comp 301 stand-off or steel comp 302 stand-off or steel comp 302b stand-off or steel comp 303 stand-off or steel comp 303se stand-off or steel comp 304 stand-off or steel comp 304l stand-off or steel comp 305 stand-off or steel comp 308 stand-off or steel comp 309 stand-off or steel comp 309s stand-off or steel comp 310 stand-off or steel comp 310s stand-off or steel comp 314 stand-off or steel comp 316 stand-off or steel comp 316l stand-off or steel comp 317 stand-off or steel comp 321 stand-off or steel comp 347 stand-off or steel comp 348 stand-off or steel comp 384 stand-off or steel comp 385 stand-off

**Material Specification:**

Mil-f-18240 military specification single material response locking feature or ms 15981 military specification single material response locking feature

**Surface Treatment:**

Oxide stand-off

**Surface Treatment Specification:**

Mil-s-13924 military specification single treatment response stand-off

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Mil-std (military Standard):**

Mil-f-18240 spec.