## NSN 5305-01-265-1193

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-265-1193 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** 1.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.870 inches and 0.875 inches **Head Height:** Between 0.495 inches and 0.500 inches **Grip Diameter:** Between 0.4995 inches and 0.5000 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches **Grip Length:** 0.940 inches Width Across Flats: Between 0.375 inches and 0.383 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** 25.0 rockwell c and 34.0 rockwell c Minimum Yield Strength: 105000 pounds per square inch **Surface Finish:** 16.0 microinches grip Material: Steel comp 305 or steel comp 316 or steel comp 321 or steel comp 347 **Material Specification:** Asme sa193 assn standard all material responses **Thread Series Designator:** Unc

Shelf Life:

N/a

## NSN 5305-01-265-1193

Close Tolerance Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0