## NSN 5305-01-265-4799

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-265-4799

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
1.000 inches
Fastener Length:
Between 0.646 inches and 0.655 inches
Head Style:
Flat extended washer
Head Diameter:
Between 0.160 inches and 0.170 inches
Head Height:
0.185 inches
Extended Washer Diameter:
Between 0.186 inches and 0.188 inches
Extended Washer Thickness:
0.060 inches
Shoulder Diameter:
0.135 inches first shoulder and 0.145 inches first shoulder
Shoulder Length:
0.125 inches first shoulder
Internal Drive Style:
Hexagon
Thread Diameter:
0.112 inches
Width Across Flats:
Between 0.937 inches and 0.952 inches
Thready Qty Per Inch (tpi):
40
Shoulder Shape:
Round first shoulder
Color:
Red head
Material:
Steel comp 303 or steel comp 410
Material Specification:
Astm a582 assn standard 1st material response or qq-s-763 federal specification 2nd material response
Surface Treatment:
Passivate
Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## NSN 5305-01-265-4799

Shoulder Screw - Page 2 of 2



Fiig: A003b0