

View Online at <https://aerobasegroup.com/nsn/5305-01-265-4803>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.428 inches and 0.478 inches

Fastener Length:

Between 0.575 inches and 0.605 inches

Head Style:

Pan

Head Diameter:

Between 0.477 inches and 0.492 inches

Head Height:

Between 0.140 inches and 0.150 inches

Grip Diameter:

Between 0.2490 inches and 0.2495 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.250 inches

Grip Length:

Between 0.177 inches and 0.197 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Surface Finish:

32.0 microinches threads

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.