NSN 5305-01-265-6391

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-265-6391

view Online at https://aerobasegroup.com/nsn/5305-01-265-6391
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.454 inches and 0.521 inches
Fastener Length:
Between 0.839 inches and 0.886 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.578 inches and 0.634 inches
Grip Diameter:
Between 0.311 inches and 0.312 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.312 inches
Grip Length:
Between 0.365 inches and 0.385 inches
Thready Qty Per Inch (tpi):
24
24 Min. Tensile Strength (psi):
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 220000 pounds per square inch
Min. Tensile Strength (psi): 220000 pounds per square inch Countersink Angle:
Min. Tensile Strength (psi): 220000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees
Min. Tensile Strength (psi): 220000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish:
Min. Tensile Strength (psi): 220000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads
Min. Tensile Strength (psi): 220000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Product Name:
Min. Tensile Strength (psi): 220000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Product Name: Navy special project
Min. Tensile Strength (psi): 220000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Product Name: Navy special project Special Features:
Min. Tensile Strength (psi): 220000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Product Name: Navy special project Special Features: Internal drive ribbed
Min. Tensile Strength (psi): 220000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Product Name: Navy special project Special Features: Internal drive ribbed Material:
Min. Tensile Strength (psi): 220000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Product Name: Navy special project Special Features: Internal drive ribbed Material: Steel comp h11
Min. Tensile Strength (psi): 220000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Product Name: Navy special project Special Features: Internal drive ribbed Material: Steel comp h11 Material Specification:
Min. Tensile Strength (psi): 220000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Product Name: Navy special project Special Features: Internal drive ribbed Material: Steel comp h11 Material Specification: Ams 6487 assn standard single material response
Min. Tensile Strength (psi): 220000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Product Name: Navy special project Special Features: Internal drive ribbed Material: Steel comp h11 Material Specification: Ams 6487 assn standard single material response Surface Treatment:
Min. Tensile Strength (psi): 220000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Product Name: Navy special project Special Features: Internal drive ribbed Material: Steel comp h11 Material Specification: Ams 6487 assn standard single material response Surface Treatment: Cadmium and chromate
Min. Tensile Strength (psi): 220000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Product Name: Navy special project Special Features: Internal drive ribbed Material: Steel comp h11 Material Specification: Ams 6487 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification:

Unjf

NSN 5305-01-265-6391

Close Tolerance Screw - Page 2 of 2



		fe	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0