NSN 5305-01-266-2867

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-266-2867 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.247 inches and 0.265 inches **Fastener Length:** Between 0.720 inches and 0.750 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **First Diameter From Head:** Between 0.127 inches and 0.133 inches **Second Diameter From Head:** Between 0.102 inches and 0.104 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.455 inches and 0.465 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.473 inches and 0.485 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Stainless steel **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002c military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-266-2867

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002c spec.