

View Online at <https://aerobasegroup.com/nsn/5305-01-266-5358>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.391 inches and 0.422 inches

Fastener Length:

Between 1.953 inches and 1.984 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.297 inches and 0.302 inches

Grip Diameter:

Between 0.189 inches and 0.190 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.075 inches first hole

Internal Drive Style:

High-torque

Thread Diameter:

0.190 inches

Grip Length:

Between 1.552 inches and 1.572 inches

Features Provided:

Cetyl alcohol lubricant and finished head

Thready Qty Per Inch (tpi):

32

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.842 inches first hole and 1.863 inches first hole

Material:

Steel comp xm-13

Material Specification:

Ams 5629 uns s13800 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

76301-st3-455 manufacturers standard and 73197-ht4024l manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0