

View Online at <https://aerobasegroup.com/nsn/5305-01-266-5358>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.391 inches and 0.422 inches

**Fastener Length:**

Between 1.953 inches and 1.984 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.297 inches and 0.302 inches

**Grip Diameter:**

Between 0.189 inches and 0.190 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole and 0.075 inches first hole

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 1.552 inches and 1.572 inches

**Features Provided:**

Cetyl alcohol lubricant and finished head

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.842 inches first hole and 1.863 inches first hole

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 uns s13800 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

76301-st3-455 manufacturers standard and 73197-ht4024l manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0