
NSN 5305-01-266-5361

Close Tolerance Screw - Page 1 of 2





Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.453 inches and 0.500 inches

Fastener Length:

Between 0.953 inches and 1.000 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.497 inches and 0.507 inches

Grip Diameter:

Between 0.249 inches and 0.250 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.250 inches

Grip Length:

Between 0.490 inches and 0.510 inches

Features Provided:

Cetyl alcohol lubricant and finished head

Thready Qty Per Inch (tpi):

28

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Thd hole in hd 0.138-32 unjc-3b; distance fm top of hd to injection port 0.240 in. Injection port 0.120 in. Lg by 0.060 in. W

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

73197-ht4075 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5305-01-266-5361

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

