

View Online at <https://aerobasegroup.com/nsn/5305-01-266-5362>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.453 inches and 0.500 inches

**Fastener Length:**

Between 0.953 inches and 1.000 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.497 inches and 0.507 inches

**Grip Diameter:**

Between 0.249 inches and 0.250 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.490 inches and 0.510 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

28

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Thd hole in hd 0.138-32 unjc-3b; distance fm top of hd to injection port 0.240 in. Injection port 0.120 in. Lg by 0.060 in. W

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 uns s13800 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

73197-ht4075 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0