NSN 5305-01-266-7366

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-266-7366



Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.488 inches and 0.538 inches **Fastener Length:** Between 0.954 inches and 0.984 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.515 inches and 0.566 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.365 inches and 0.385 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads **Product Name:** Navy special project Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response **Surface Treatment: Passivate**

Unjf

Surface Treatment Specification:

Thread Series Designator:

Qq-p-35 federal specification single treatment response

NSN 5305-01-266-7366

Close Tolerance Screw - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

80205-nas1581 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0