

View Online at <https://aerobasegroup.com/nsn/5305-01-266-8304>

**Thread Class:**

2a

**Thread Direction:**

Left-hand

**Thread Length:**

Between 1.535 inches and 1.565 inches

**Fastener Length:**

2.105 inches

**Head Style:**

Flat extended washer

**Head Diameter:**

Between 0.140 inches and 0.144 inches

**Head Height:**

0.275 inches

**Extended Washer Diameter:**

0.450 inches

**Extended Washer Thickness:**

0.040 inches

**First Diameter From Head:**

Between 0.186 inches and 0.187 inches

**Second Diameter From Head:**

0.125 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.080 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.205 inches

**Point Style:**

Flat

**Internal Drive Style:**

W/o internal drive

**Thread Diameter:**

0.164 inches

**Hole Quantity:**

1

**Hole Type:**

Threaded

**Thready Qty Per Inch (tpi):**

40

**Hole Thready Qty Per Inch (tpi):**

80

**Hole Configuration Style:**

Round longitudinal hole

**Externally Relieved Body Diameter Quantity:**

1

**Hole Thread Diameter:**

0.060 inches

**Special Features:**

Special four pointed end

**Color:**

Black

**Material:**

Steel comp 303

**Material Specification:**

Astm a582 assn standard single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924, class 4 military specification single treatment response

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.