Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-266-8304

Thread Class:
2a
Thread Direction:
Left-hand
Thread Length:
Between 1.535 inches and 1.565 inches
Fastener Length:
2.105 inches
Head Style:
Flat extended washer
Head Diameter:
Between 0.140 inches and 0.144 inches
Head Height:
0.275 inches
Extended Washer Diameter:
0.450 inches
Extended Washer Thickness:
0.040 inches
First Diameter From Head:
Between 0.186 inches and 0.187 inches
Second Diameter From Head:
0.125 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.080 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
0.205 inches
Point Style:
Flat
Internal Drive Style:
W/o internal drive
Thread Diameter:
0.164 inches
Hole Quantity:
1
Hole Type:
Threaded
Thready Qty Per Inch (tpi):
40
Hole Thready Qty Per Inch (tpi):
80
Hole Configuration Style:
Round longitudinal hole

Externally Relieved Body Screw - Page 2 of 2



Externally Relieved Body Diameter Quantity:

1

Hole Thread Diameter:

0.060 inches

Special Features:

Special four pointed end

Color:

Black

Material:

Steel comp 303

Material Specification:

Astm a582 assn standard single material response

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924, class 4 military specification single treatment response

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.