NSN 5305-01-266-8304

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-266-8304 **Thread Class:** 2a **Thread Direction:** Left-hand Thread Length: Between 1.535 inches and 1.565 inches **Fastener Length:** 2.105 inches **Head Style:** Flat extended washer **Head Diameter:** Between 0.140 inches and 0.144 inches **Head Height:** 0.275 inches **Extended Washer Diameter:** 0.450 inches **Extended Washer Thickness:** 0.040 inches **First Diameter From Head:** Between 0.186 inches and 0.187 inches **Second Diameter From Head:** 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.080 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.205 inches Point Style: Flat **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.164 inches **Hole Quantity: Hole Type:** Threaded Thready Qty Per Inch (tpi): 40 Hole Thready Qty Per Inch (tpi): **Hole Configuration Style:**

Round longitudinal hole

NSN 5305-01-266-8304

Externally Relieved Body Screw - Page 2 of 2



Externally Relieved Body Diameter Quantity:
1
Hole Thread Diameter:
0.060 inches
Special Features:
Special four pointed end
Color:
Black
Material:
Steel comp 303
Material Specification:
Astm a582 assn standard single material response
Surface Treatment:
Oxide
Surface Treatment Specification:
Mil-c-13924, class 4 military specification single treatment response
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):
Mil-c-13924 spec