Passivate

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-266-8341

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.264 inches
Fastener Length:
Between 0.343 inches and 0.375 inches
Head Style:
Pan
Head Diameter:
Between 0.306 inches and 0.322 inches
Head Height:
Between 0.105 inches and 0.115 inches
Washer Quantity:
2
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Secondary Washer Relationship To Primary Washer:
Not identical
Secondary Washer Style:
Flat
Primary Washer Outside Diameter:
0.293 inches
Secondary Washer Outside Diameter:
Between 0.307 inches and 0.317 inches
Primary Washer Style:
Split helical ring
Primary Washer Material Thickness:
0.040 inches
Secondary Washer Material Thickness:
Between 0.013 inches and 0.019 inches
Material:
Steel comp 302 secondary washer or steel comp 304 secondary washer
Material Specification:
Qq-s-763 federal specification all material responses fastener
Surface Treatment:
Passivate

NSN 5305-01-266-8341

Assembled Washer Screw - Page 2 of 2



Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Specification Data:

80205-nas1301 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5059 spec.