

View Online at <https://aerobasegroup.com/nsn/5305-01-266-8364>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.651 inches and 0.734 inches

Fastener Length:

Between 0.734 inches and 0.766 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.303 inches and 0.313 inches

Head Height:

Between 0.185 inches and 0.190 inches

Shank Unthreaded Hole Diameter:

0.061 inches first hole and 0.065 inches first hole

Internal Drive Style:

Hexagon

Thread Diameter:

0.190 inches

Width Across Flats:

Between 0.156 inches and 0.159 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

80.0 rockwell b

Criticality Code Justification:

Zzzy

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.724 inches first hole and 0.756 inches first hole

Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

Surface Treatment:

Passivate

Special Test Features:

Special quality control testing

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Test Data Document:

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Reference Number Differentiating Characteristics:

As differentiated by material which must conform to ships parts control center special quality control provisions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0