

View Online at <https://aerobasegroup.com/nsn/5305-01-266-8370>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

1.063 inches

**Fastener Length:**

Between 1.438 inches and 1.500 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.195 inches and 0.211 inches

**Width Between Flats:**

Between 0.489 inches and 0.500 inches

**Shank Unthreaded Hole Diameter:**

0.074 inches first hole and 0.082 inches first hole

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

70000 pounds per square inch

**Hardness Rating:**

235.0 brinell b

**Minimum Yield Strength:**

40000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.385 inches first hole and 1.403 inches first hole

**Surface Finish:**

63.0 microinches threads

**Material:**

Steel comp 410 or steel comp 416 or steel comp 430

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

2 type and 10p style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0