

View Online at <https://aerobasegroup.com/nsn/5305-01-266-8582>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.169 inches and 0.219 inches

Fastener Length:

Between 0.661 inches and 0.691 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.193 inches and 0.226 inches

Grip Diameter:

Between 0.1105 inches and 0.1115 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.112 inches

Grip Length:

Between 0.428 inches and 0.438 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

63.0 microinches bearing surface of head

Material:

Iron alloy 660

Material Specification:

Ms5731 assn standard single material response or ams5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas7500 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0