NSN 5305-01-266-8585

Close Tolerance Screw - Page 1 of 2



AeroBase

View Online at https://aerobasegroup.com/nsn/5305-01-266-8585

| Thread Class: | |
|------------------------|---|
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| Between 0.378 inche | es and 0.428 inches |
| Fastener Length: | |
| Between 0.950 inche | es and 0.980 inches |
| Head Style: | |
| Flat countersunk | |
| Head Diameter: | |
| Between 0.350 inche | es and 0.399 inches |
| Grip Diameter: | |
| Between 0.2485 incl | nes and 0.2495 inches |
| Internal Drive Style | |
| Offset cruciform (tore | que set) |
| Thread Diameter: | |
| 0.250 inches | |
| Grip Length: | |
| Between 0.552 inche | es and 0.572 inches |
| Thready Qty Per In | ch (tpi): |
| 28 | |
| Min. Tensile Streng | yth (psi): |
| 160000 pounds per | square inch |
| Hardness Rating: | |
| 36.0 rockwell c and | I 40.0 rockwell c |
| Countersink Angle | : |
| Between 99.0 degre | es and 101.0 degrees |
| Surface Finish: | |
| 63.0 microinches be | aring surface of head |
| Material: | |
| Iron alloy 660 | |
| Material Specificati | ion: |
| Ams5731 assn stand | dard single material response or ams5732 assn standard single material response or ams5737 assn standard single |
| material response | |
| Surface Treatment: | |
| Cadmium and chror | nate |
| Surface Treatment | Specification: |
| Qq-p-416 type 2 cl 2 | 2 federal specification single treatment response |
| Thread Series Desi | gnator: |
| Unjf | |
| Specification Data: | |

80205-nas1581 professional/industrial association standard

NSN 5305-01-266-8585

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

