

View Online at <https://aerobasegroup.com/nsn/5305-01-266-9191>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.438 inches and 0.500 inches

**Fastener Length:**

0.500 inches

**Head Style:**

Oval countersunk undercut

**Head Diameter:**

Between 0.292 inches and 0.332 inches

**Head Height:**

Between 0.101 inches and 0.123 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

Between 80.0 degrees and 82.0 degrees

**Screw Material:**

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

**Screw Surface Treatment:**

Passivate

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0