

View Online at <https://aerobasegroup.com/nsn/5305-01-266-9199>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.166 inches and 0.259 inches

Fastener Length:

Between 0.344 inches and 0.375 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.340 inches and 0.385 inches

Locking Feature:

Patch threads or strip threads

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

60000 pounds per square inch

Countersink Angle:

Between 80.0 degrees and 82.0 degrees

Material:

Steel comp 1008 or steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1025 or steel comp 1030 or steel comp 1035 or steel comp 1040 or steel comp 1045 or steel comp 1050 or steel comp 1095 or steel comp 1213 or steel comp 1115 or steel comp 1117 or steel comp 1118 or steel comp 1137 or steel comp 1141 or steel comp 1144 or steel comp 1151 or steel comp 12114 or steel comp 1211 or steel comp 1212 or steel comp 1213 or steel comp 1215 or steel comp 1330

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Specification Or Standard:

3 type and 2c style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig: