

View Online at <https://aerobasegroup.com/nsn/5305-01-266-9361>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.261 inches and 0.311 inches

**Fastener Length:**

Between 0.583 inches and 0.613 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.339 inches and 0.341 inches

**Grip Diameter:**

Between 0.1085 inches and 0.1095 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.302 inches and 0.322 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 8740 or steel comp 4340

**Material Specification:**

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Ps13143 cl 3 type 2 caged 85277 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6049 spec.