

View Online at <https://aerobasegroup.com/nsn/5305-01-266-9833>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.122 inches and 0.142 inches

Fastener Length:

Between 0.274 inches and 0.284 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.256 inches and 0.270 inches

Head Height:

Between 0.087 inches and 0.097 inches

First Diameter From Head:

Between 0.096 inches and 0.106 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.132 inches and 0.162 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

80000 pounds per square inch

Externally Relieved Body Diameter Quantity:

1

Color:

Black

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924, class 3 military specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.