

View Online at <https://aerobasegroup.com/nsn/5305-01-267-2875>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.085 inches

Fastener Length:

Between 0.110 inches and 0.140 inches

Head Style:

Pan

Head Diameter:

Between 0.104 inches and 0.116 inches

Head Height:

Between 0.031 inches and 0.039 inches

Internal Drive Style:

Slot

Thread Diameter:

0.060 inches

Thready Qty Per Inch (tpi):

80

Min. Tensile Strength (psi):

80000 pounds per square inch

Screw Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Screw Material Specification:

Qq-s-763 federal specification all material responses or 66 federal standard all material responses

Screw Surface Treatment:

Oxide

Color:

Black

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0