## NSN 5305-01-267-9014

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-267-9014 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.631 inches **Fastener Length:** Between 0.720 inches and 0.750 inches **Head Style:** Pan **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Plastic locking feature **Material Specification:** Mil-f-18240 military specification single material response locking feature **Surface Treatment:** Cadmium fastener and chromate fastener **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response fastener **Thread Series Designator:** 

Unjf

**Specification Data:** 

80205-nas8104 professional/industrial association standard

Shelf Life:

N/a

## NSN 5305-01-267-9014

Socket Head Cap Screw - Page 2 of 2



	• -		
In	ıŧ	( )t	Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-18240 spec.