## NSN 5305-01-268-0146

Close Tolerance Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-268-0146 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.444 inches and 0.494 inches **Fastener Length:** Between 1.329 inches and 1.359 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.497 inches and 0.507 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.865 inches and 0.885 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** 1thd hole in top of head 0.138-32 unjc-3b; threaded hole 0.300 in. Min 0.345 in. Maximum dp; counterbore 0.145 in. Min lg, 0.150 in. Maximum Ig; 0.060 in. Wide in unthreaded shank; distant from top of head to beginning of injection port 0.570 Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard 1st material response and ams 4967 assn standard 2nd material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A003b0