NSN 5305-01-268-1181

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-268-1181 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.370 inches **Fastener Length:** 0.660 inches **Head Style:** Hexagon **Head Height:** 0.180 inches Width Between Flats: 0.312 inches **First Diameter From Head:** Between 0.153 inches and 0.154 inches **Second Diameter From Head:** Between 0.105 inches and 0.107 inches Third Diameter From Head: Between 0.149 inches and 0.154 inches **Fourth Diameter From Head:** 0.104 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.134 inches and 0.142 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.183 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.210 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 0.290 inches **Point Style:** Flat **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** 2

Material:

Steel comp 303

NSN 5305-01-268-1181

Externally Relieved Body Screw - Page 2 of 2



Material Specification:
Astm a582 cond a assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 type 4 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0