

View Online at <https://aerobasegroup.com/nsn/5305-01-268-2666>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.938 inches and 1.125 inches

**Fastener Length:**

Between 1.063 inches and 1.125 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.716 inches and 0.740 inches

**Head Height:**

Between 0.244 inches and 0.261 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Screw Material:**

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Astm a380 assn standard single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0