NSN 5305-01-268-3646

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-268-3646

	ead Class:
3a	
Thr	ead Direction:
Rig	ht-hand
Thr	ead Length:
1.37	75 inches
Fas	stener Length:
Bet	ween 1.690 inches and 1.750 inches
Hea	ad Style:
Flat	chamfer
Hea	ad Diameter:
3et [,]	ween 0.642 inches and 0.656 inches
Hea	ad Height:
Bet	ween 0.430 inches and 0.437 inches
_00	king Feature:
Pate	ch threads or pellet threads or strip threads
nte	ernal Drive Style:
Hex	kagon
Γhr	ead Diameter:
0.43	37 inches
Wic	Ith Across Flats:
3et [,]	ween 0.375 inches and 0.379 inches
Γhr	eady Qty Per Inch (tpi):
4	
Min	. Tensile Strength (psi):
300	00 pounds per square inch
Har	dness Rating:
80.0) rockwell b
Min	imum Yield Strength:
300	00 pounds per square inch
Mat	erial:
Ste	el comp 302 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or steel comp xm-7 fastener
Mat	erial Specification:
Astr	m a493 assn standard all material responses fastener
Sur	face Treatment:
Pas	sivate fastener
Sur	face Treatment Specification:
Qq-	p-35 federal specification single treatment response fastener
Thr	ead Series Designator:
Unr	c
Spe	ecification Data:
	05-nas1352 professional/industrial association standard

NSN 5305-01-268-3646

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

