NSN 5305-01-268-3646

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-268-3646

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.375 inches
Fastener Length:
Between 1.690 inches and 1.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.642 inches and 0.656 inches
Head Height:
Between 0.430 inches and 0.437 inches
Locking Feature:
Patch threads or pellet threads or strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.437 inches
Width Across Flats:
Between 0.375 inches and 0.379 inches
Thready Qty Per Inch (tpi):
14
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or steel comp xm-7 fastener
Material Specification:
Astm a493 assn standard all material responses fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener
Thread Series Designator:
Unrc
Specification Data:

80205-nas1352 professional/industrial association standard

NSN 5305-01-268-3646

Socket Head Cap Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0