NSN 5305-01-268-8812

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-268-8812 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.574 inches and 0.624 inches **Fastener Length:** Between 2.022 inches and 2.052 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.826 inches and 0.888 inches **Grip Diameter:** Between 0.4365 inches and 0.4370 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.438 inches **Grip Length:** Between 1.428 inches and 1.448 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-268-8812

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0