Socket Head Cap Screw - Page 1 of 2



xm-7

View Online at https://aerobasegroup.com/nsn/5305-01-268-9096

Thread Class:
За
Thread Direction:
Right-hand
Thread Length:
1.500 inches
Fastener Length:
Between 2.670 inches and 2.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.735 inches and 0.750 inches
Head Height:
Between 0.492 inches and 0.500 inches
Hole Diameter:
Between 0.061 inches and 0.067 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.500 inches
Width Across Flats:
Between 0.375 inches and 0.379 inches
Hole Quantity:
6
Ноје Туре:
Drilled
Thready Qty Per Inch (tpi):
13
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Material:
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response

NSN 5305-01-268-9096

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0