

View Online at <https://aerobasegroup.com/nsn/5305-01-269-5125>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.484 inches and 0.516 inches

Fastener Length:

Between 0.593 inches and 0.625 inches

Head Style:

Pan

Head Diameter:

Between 0.306 inches and 0.322 inches

Head Height:

Between 0.307 inches and 0.317 inches

Washer Quantity:

2

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

35.0 rockwell c primary washer and 43.0 rockwell c primary washer

Secondary Washer Relationship To Primary Washer:

Not identical

Secondary Washer Style:

Flat

Primary Washer Outside Diameter:

0.293 inches

Secondary Washer Outside Diameter:

Between 0.307 inches and 0.317 inches

Primary Washer Style:

Split helical ring

Primary Washer Material Thickness:

0.040 inches

Secondary Washer Material Thickness:

Between 0.013 inches and 0.019 inches

Material:

Steel comp 302 secondary washer or steel comp 304 secondary washer

Material Specification:

Qq-s-763 federal specification all material responses fastener

Surface Treatment:

Passivate secondary washer

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response secondary washer

Thread Series Designator:

Unc

Specification Data:

80205-nas1301 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5059 spec.