Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-269-6263



# 2a **Thread Direction:** Right-hand **Thread Length:** Between 0.658 inches and 0.750 inches **Fastener Length:** Detween 0.750 inches

**Thread Class:** 

Between 0.720 inches and 0.750 inches

## Head Style:

Watertight

Head Diameter:

Between 0.357 inches and 0.403 inches

## **Head Height:**

Between 0.122 inches and 0.133 inches

## Locking Feature:

Patch threads or pellet threads or strip threads

#### **Internal Drive Style:**

Cross recess type 1

# Thread Diameter:

0.190 inches

# **Features Provided:**

O ring

Thready Qty Per Inch (tpi):

32

# Material:

Steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or steel comp xm-7 fastener

# Material Specification:

Mil-s-82496 military specification single material response ring

# Surface Treatment:

Passivate fastener

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

# **Thread Series Designator:**

Unf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

NSN 5305-01-269-6263

Socket Head Cap Screw - Page 2 of 2

Mil-std (military Standard):

Mil-s-82496 spec.

