Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-269-6268

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.658 inches and 0.750 inches
Fastener Length:
Between 0.720 inches and 0.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.303 inches and 0.312 inches
Head Height:
Between 0.185 inches and 0.190 inches
Hole Diameter:
Between 0.044 inches and 0.050 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
Between 0.156 inches and 0.159 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unrf

NSN 5305-01-269-6268

Socket Head Cap Screw - Page 2 of 2



Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0