Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-269-9222

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.200 inches
Fastener Length:
Between 0.516 inches and 0.536 inches
Head Style:
Fillister
Head Diameter:
Between 0.306 inches and 0.322 inches
Head Height:
Between 0.105 inches and 0.115 inches
First Diameter From Head:
Between 0.114 inches and 0.124 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.321 inches
Point Style:
Flat
Internal Drive Style:
Slot
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
80000 pounds per square inch
Externally Relieved Body Diameter Quantity:
1
Product Name:
Navy special project
Material:
Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or
steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or
steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel
comp 385
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 type 4 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0