## NSN 5305-01-270-0074

Close Tolerance Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-270-0074 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 0.677 inches and 0.697 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.375 inches **Head Height:** Between 0.121 inches and 0.133 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.084 inches and 0.104 inches Thready Qty Per Inch (tpi): 32 **Special Features:** Two keyways along threads 180 degrees apart; width of keyways 0.044 in. Min. And 0.054 in. Max Material: Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 **Material Specification:** Qq-s-763 federal specification all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

Fiig: A003b0

No

**Demilitarization:**