

View Online at <https://aerobasegroup.com/nsn/5305-01-270-1219>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.173 inches and 0.188 inches

Fastener Length:

Between 0.797 inches and 0.827 inches

Head Style:

Knurled no. 2

Head Diameter:

Between 0.307 inches and 0.327 inches

Head Height:

Between 0.161 inches and 0.213 inches

Point Length:

0.125 inches

Point Diameter:

Between 0.079 inches and 0.095 inches

First Diameter From Head:

Between 0.090 inches and 0.105 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.489 inches and 0.509 inches

Point Style:

Cone

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

1

Point Chamfer Angle:

Between 55.0 degrees and 65.0 degrees

Material:

Steel comp 203ez or steel comp 303 or steel comp 303 plus x or steel comp 303ma or steel comp 303pb or steel comp 303se or steel comp 416 or steel comp 416 plus x or steel comp 416se or steel comp 430f or steel comp 420fse or steel comp 420f or steel comp 430fse or steel comp 440f

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0