## NSN 5305-01-270-1706



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-270-1706 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.251 inches and 0.301 inches **Fastener Length:** Between 1.199 inches and 1.229 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **Locking Feature:** Patch threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 63.0 microinches bearing surface of head Material: Steel comp e4340 fastener or steel comp 8740 fastener **Material Specification:** Mil-s-5000 military specification 1st material response fastener or mil-s-6049 military specification 2nd material response fastener or ams6322 assn standard 2nd material response fastener **Surface Treatment:** Cadmium fastener and chromate fastener **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response fastener **Thread Series Designator:** 

Unjf

**Specification Data:** 

80205-nas7701 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5305-01-270-1706

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.