

View Online at <https://aerobasegroup.com/nsn/5305-01-270-2948>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.077 inches and 0.159 inches

**Fastener Length:**

Between 0.172 inches and 0.204 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.177 inches and 0.225 inches

**Locking Feature:**

Patch threads

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp 4140 fastener or steel comp e4340 fastener or steel comp 8740 fastener

**Material Specification:**

Mil-s-5626 military specification 1st material response fastener or mil-s-5000 military specification 2nd material response fastener or mil-s-6049 military specification 3rd material response fastener

**Surface Treatment:**

Cadmium fastener and chromate fastener

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response fastener

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.