

View Online at <https://aerobasegroup.com/nsn/5305-01-270-3698>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.444 inches and 0.494 inches

**Fastener Length:**

Between 1.142 inches and 1.172 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.497 inches and 0.507 inches

**Grip Diameter:**

Between 0.2490 inches and 0.2495 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.678 inches and 0.698 inches

**Thready Qty Per Inch (tpi):**

28

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

1thd hole in top of head 0.138-32 unjc-3b; threaded hole 0.300 in. Min 0.345 in. Maximum dp; counterbore, 0.145 in. Min lg, 0.150 in. Maximum lg; 0.060 in. Wide in. Wide in unthreaded shank; distant from top of head to beginning of injection port 0.390

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard 1st material response and ams 4967 assn standard 2nd material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0