NSN 5305-01-270-3897

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-270-3897 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.419 inches and 0.500 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches **Locking Feature:** Patch threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.094 inches and 0.095 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 38.0 rockwell c fastener and 45.0 rockwell c fastener Material: Steel fastener **Material Specification:** Mil-f-18240 military specification single material response locking feature **Surface Treatment:** Cadmium fastener and chromate fastener **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response fastener **Thread Series Designator:** Unc **Specification Or Standard:** 4 type

Shelf Life:

N/a

NSN 5305-01-270-3897

Socket Head Cap Screw - Page 2 of 2



		• -						
ш	ın	ıt (r 1t	ΝЛ	മാ	CI.	ire:	•

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-18240 spec.