

View Online at <https://aerobasegroup.com/nsn/5305-01-270-5443>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.273 inches and 0.322 inches

**Fastener Length:**

Between 0.657 inches and 0.687 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.292 inches and 0.313 inches

**Head Height:**

Between 0.123 inches and 0.130 inches

**First Diameter From Head:**

0.115 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.365 inches and 0.385 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Color:**

Green

**Material:**

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

**Surface Treatment:**

Primer and paint

**Surface Treatment Specification:**

Mil-p-23377, type 1 military specification 1st treatment response and mil-c-22750, type 1, color no. 24064 per fed-std-595 military specification 2nd treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-p-23377 spec.